



Customer Specification Endurosaf™ Aprons

PRODUCT NOMENCLATURE

Manufacturing Code(s): 56-800, 56-801 and 56-802
Manufacturing Name: Endurosaf™ Aprons
Marketing Glove ASPN Code(s): See Below (“Styles & Colors Within Series”)

PRODUCT DESCRIPTION

Product Classification:	Endurosaf™ Apron	Composition:	Enduro 2000™
Color:	White, Yellow & Blue	Finish:	Smooth
Thickness:	8-9 Mils	Printing:	None
Weight:	7.5 – 8.0 Oz./Sq. Yd.	Dimensions:	See Below
Edge Finish:	Die Cut	Packaging:	2 Dozen Per Case

OUTSTANDING CHARACTERISTICS & APPLICATIONS

- ◆ Offers a unique combination of characteristics that outperform neoprene, nitrile, vinyl and other films.
- ◆ Light weight, yet strong and exceptionally resistant to abrasion, chemicals, oils and fats.
- ◆ Outstanding tear and puncture strength.
- ◆ Soft, comfortable, easy to clean and remains flexible in cold temperatures.
- ◆ Environmentally friendly...may be buried or incinerated without harm to the environment.
- ◆ Dielectrically sealed neck strap is strong and adjustable, with a non-corrosive, non-absorbent plastic buckle.
- ◆ Dielectrically sealed side ties are durable and adjustable for added wear and comfort.
- ◆ Component materials comply with FDA regulations for food contact.
- ◆ Passes Test ASTM F 903 “Resistance of Materials Used in Protective Clothing to Penetration by Liquids” against hot cooking oil at 375-400° F.
- ◆ **APPLICATIONS:** Medical, Cleanrooms, Laboratories, Food processing, Chemical processing, Pharmaceutical, Janitorial

STYLES/COLORS WITHIN SERIES

STYLE	ASPN CODE	COLOR/DIMENSIONS
56-800 (SAF-35W)	951921	White 27” x 35”
56-800 (SAF-45W)	951922	White 35” x 45”
56-800 (SAF-50W)	951923	White 35” x 50”
56-801 (SAF-35Y)	951924	Yellow 27” x 35”
56-801 (SAF-45Y)	951925	Yellow 35” x 45”
56-801 (SAF-50Y)	951926	Yellow 35” x 50”
56-802 (SAF-35B)	951927	Blue 27” x 35”
56-802 (SAF-45B)	951928	Blue 35” x 45”
56-802 (SAF-50B)	951929	Blue 35” x 50”

GUARANTEE

These products are manufactured to rigid specifications under strict conditions of process and quality control set forth by Ansell. They are guaranteed against defect in workmanship or material and will be replaced or credited if returned for examination. This guarantee does not apply to deterioration caused by excessive wear, age, accident, or prolonged exposure to strong solvents or direct ultraviolet light.

GENERAL INFORMATION

SHELF LIFE: Three (3) years in cool, covered conditions. Extended exposure to direct sunlight or excessive heat may reduce shelf life.
MFG LOCATION: Thomasville, NC, USA

Originator: Paul McMorrow **Date:** 12/21/01
Revised By: Paul McMorrow **Date:** 04/21/06 **Revision #: 1** (Added ASTM 903 Penetration Test)

NEITHER THIS NOR ANY STATEMENT MADE BY OR ON BEHALF OF ANSELL HEREIN IS A WARRANTY THAT ANY PRODUCT IS FIT FOR A PARTICULAR PURPOSE AND ANSELL SHALL NOT BE LIABLE TO ANYONE WITH RESPECT TO THIS INFORMATION.

This document is the property of Ansell and the information contained herein is proprietary to Ansell.