



Medium Duty Manual Countertop Convection Ovens

Small Footprint - Large Production

- High performance • High reliability • Versatility of use
- Stainless steel exterior & interior
- Optimum thermal insulation • Uniform baking



OV-023



120 Volt

OV-013



120 Volt

OV-003

COMMON FEATURES

- Advanced airflow design for even baking
- Heavy-duty squirrel cage fan moves more air in less time
- Manual controls: Time, Temperature
- Heat settings from 175°-500° F
- 60 minute timer or continuous on
- Heavy duty stainless steel construction
- Heavy duty door & hinge construction
- High temperature ball-bearing motor for long-lasting use
- 2.5" between shelves
- "Cool-touch" double wall glass door
- Reinforced door design
- Oven cavity is wrapped in high "R" value insulation
- NSF, UL through MET Standards / listed by UNOX S.r.l.
- Freight Class 200
- 2 Year Limited Warranty (90 days on gaskets & lights; 30 days on glass; one year on motor)
- Stands available for Half Size Oven Models



NEMA 5-15P Plug



NEMA 6-15P Plug

	OV-023	OV-013	OV-003
Sheet pan capacity	4 half size	3 half size	3 quarter size
Cooking Chamber	W: 18-3/4" x D: 13-3/4" x H: 11-3/4" (1.75 cu.ft.)	W: 18-3/4" x D: 13-3/4" x H: 9" (1.34 cu.ft.)	W: 14-1/8" x D: 11-1/4" x H: 9" (.83 cu. ft.)
Unit Dimensions	W: 23-5/8" x D: 23-3/4" x H: 18-5/8"	W: 23-5/8" x D: 23-3/4" x H: 15-3/4"	W: 18-7/8" x D: 21-1/2" x H: 15-3/4"
Unit Weight	62 lbs.	55 lbs.	42 lbs.
Carton Dimensions & Cube	W: 42" x D: 48" x H: 25-1/4" (*29.46 cu. ft.)	W: 26-3/4" x D: 25-3/4" x H: 17-1/2" (7 cu. ft.)	W: 20-7/8" x D: 24" x H: 17-3/8" (5.04 cu. ft.)
Shipping Weight	120 lbs. (*incl 40 lb. skid.)	67 lbs.	55 lbs.
Electrical (Single Phase)	208-240V / 2,700W / 11.25 A	120V / 1,450W / 12 A	120V / 1,450W / 12 A
Plug	NEMA 6-15P Plug	NEMA 5-15P Plug	NEMA 5-15P Plug
Distance between shelves	2.5"	2.5"	2.5"
UPC Code	654796-53400-5	654796-53350-3	654796-53250-6

For more information, please contact Cadco, Ltd, 200 International Way, Winsted, CT 06098
Tel. (860)738-2500 • Fax (860) 738-9772 • E-mail: info@cadco-ltd.com • Web site: cadco-ltd.com

Due to continual product improvement, all product specifications, designs and prices are subject to change without notice.

3/16/2017 RV13