

Universal Runner Heater Proofer Designed for Hubert Company

Description

HC 1816 HPCU- Full Size Non-Insulated Hubert # 63321

HC 1816HPICU Insulated Hubert #64028

Heated Holding Cabinet with Clear Lexan Door helps you to see in the unit without opening the door.

Proof temperature range from 80 to 105 degree.

Heat settings can be adjusted to your needs. The holding mode that can reach up to 180 degrees fahrenheit, these cabinet are perfect for storing a wide variety of ready-to-serve PREHEATED dishes.

A total of 16 pan slides holds full and half sheet pans by the bottom & full, half and third size steam table pans by the edge.

The door has both magnets and a tight-fitting gasket to help maintain proper temperature.

Controls are located on the unit's bottom control drawer. Drawer can be removed for service

Requires a 120V electrical connection 15 amp dedicated service.

Comes standard with a cord and NEMA 5-15P plug. UL and NSF Listed.

HC1816HPCU Full Size non Insulated

Great for general use.
Cabinet will help keep product hot or be used for basic proofing needs.



Technical Data

| | Non insulated HC18316-HPCU | Insulated HC 18316 HPICU |
|---------------------|----------------------------|--------------------------|
| Hubert model number | 63321 | 64028 |
| Dimensions | 21" x 31" x 68 | 21" x 31" x 68 |
| Watts | 1440 W | 1440 W |
| Amps / Hertz | 14 Amp / 60 H | 14 Amp / 60 H |
| Capacity | 16 slides | 16 slides |
| Spacing | 3" | 3" |
| Temperature | 85 to 180 Degrees | 85 to 180 Degrees |
| Type | non insulated | insulated |
| UL | UL listed | UL listed |
| Casters | 5" swivel with 2 brakes | 5" swivel with 2 brakes |
| NSF | Yes | Yes |

HC1816HPICU Full Size Insulated

Insulated Cabinet has better temperature recovery and lower energy use.
Preferred unit by Schools Districts and Health Departments.

