SAFETY DATA SHEET

1. Identification

Product number	26521 - CP8446HUBERT
Product identifier	HUBERT W.B. STAINLESS STEEL CLEANER
Revision date	10-13-2014
Company information	HUBERT 9555 DRY FORK RD. HARRISON, OH 45038 United States
Company phone	General Assistance: 1-800-543-7374
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	08
Supersedes date	10-02-2014
Recommended use	Cleaner
Recommended restrictions	None known.

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Aspiration hazard	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 3

OSHA defined hazards

Label elements



Danger
Extremely flammable aerosol. May be fatal if swallowed and enters airways.
Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.
If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.
Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.
None known.
26.36% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 26.36% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	10 - 20
Distillates (Petroleum), Hydrotreated Light		64742-47-8	10 - 20

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	2.5 - 10
Polydimethylsiloxane		63148-62-9	1 - 2.5
Other components below reportable lev	vels		60 - 80

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation. Aspiration may cause pulmonary edema and pneumonitis.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.
General fire hazards	Extremely flammable aerosol.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled

protective equipment and clothing during clean-up. Do not touch damaged containers or spilled emergency procedures material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if Methods and materials for you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. containment and cleaning up Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use. Avoid discharge into drains, water courses or onto the ground. **Environmental precautions** 7. Handling and storage Precautions for safe handling Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Use only outdoors or in a well-ventilated area. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Provide adequate ventilation. Avoid breathing mist or vapor. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding Conditions for safe storage, 50°C/122 °F. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Keep including any incompatibilities in a cool place. Store away from incompatible materials (see Section 10 of the SDS). Level 1 Aerosol.

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm
US. ACGIH Threshold Lim	nit Values	
Components	Туре	Value
Butane (CAS 106-97-8)	STEL	1000 ppm
US. NIOSH: Pocket Guide	to Chemical Hazards	
Components	Туре	Value
Butane (CAS 106-97-8)	TWA	1900 mg/m3
		800 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm
ological limit values	No biological exposure limits noted f	or the ingredient(s).
propriate engineering ntrols	Explosion-proof general and local exhaust ventilation.	
lividual protection measure	s, such as personal protective equipn	nent
Eye/face protection	Wear safety glasses with side shield	s (or goggles).
Hand protection	Wear protective gloves.	
Skin protection		
Other	Wear suitable protective clothing.	
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
neral hygiene nsiderations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	5.6 - 6.6 estimated
Melting point/freezing point	Not available.
Initial boiling point and boiling range	229.79 °F (109.88 °C) estimated
Flash walut	1FC 0 °F (101 1 °C) Dranallant actimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
-	· / ·
Evaporation rate	Not available. Not available.
Evaporation rate Flammability (solid, gas)	Not available. Not available.
Evaporation rate Flammability (solid, gas) Upper/lower flammability or exp Flammability limit - lower	Not available. Not available. Iosive limits
Evaporation rate Flammability (solid, gas) Upper/lower flammability or exp Flammability limit - lower (%) Flammability limit - upper	Not available. Not available. Iosive limits Not available.

Vapor pressure	47 - 67 psig @ 70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	392 °F (200 °C) estimated
Decomposition temperature	Not available.
Viscosity	Not available.
Other information Specific gravity	0.948 estimated
10. Stability and reactivity	,
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous	No dangerous reaction known under conditions of normal use.

reactions	
Conditions to avoid	Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Fluorine. Chlorine. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in lung edema or pneumonia.
Inhalation	Not available.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.

Information on toxicological effects

Acute toxicity	Expected to be a low hazard for u	Expected to be a low hazard for usual industrial or commercial handling by trained personnel.	
Product	Species	Test Results	
16 OZ HUBERT W.B. STAIN	NLESS STEEL CLEANER (CAS Mixture)		
Acute			
Dermal			
LD50	-	30739.2988 mg/kg estimated	
	Rabbit	6277.4639 mg/kg, 24 Hours estimated	
	Rat	6796 mg/kg	
Inhalation			
LC100	Cat	610.998 % estimated	
LC50	Mouse	8397.8271 mg/l, 120 Minutes estimated	
		353.0211 %, 120 Minutes estimated	
		108.6219 mm/l, 2 Hours estimated	
	Rat	88411.4063 ppm, 4 Hours estimated	
		14.3747 mg/l, 4 Hours estimated	
Oral			
LD50	Rat		

Mouse Rat .ight (CAS 647 Rabbit Rat Rat Mouse Rat	742-47-8)	1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l > 2000 mg/kg > 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg	
Rat Light (CAS 647 Rabbit Rat Rat Mouse	742-47-8)	52 %, 120 Minutes 1355 mg/l > 2000 mg/kg > 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Rat Light (CAS 647 Rabbit Rat Rat Mouse	742-47-8)	52 %, 120 Minutes 1355 mg/l > 2000 mg/kg > 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Rat Light (CAS 647 Rabbit Rat Rat Mouse	742-47-8)	52 %, 120 Minutes 1355 mg/l > 2000 mg/kg > 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
ight (CAS 647 Rabbit Rat Rat Mouse	742-47-8)	1355 mg/l > 2000 mg/kg > 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
ight (CAS 647 Rabbit Rat Rat Mouse	742-47-8)	 > 2000 mg/kg > 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes 	
Rabbit Rat Rat Mouse	742-47-8)	> 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Rat Rat Mouse		> 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Rat Rat Mouse		> 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Rat Rat Mouse		> 2000 mg/kg, 24 Hours > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Rat Mouse		 > 7.5 mg/l, 6 Hours > 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes 	
Rat Mouse		> 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Rat Mouse		> 4.6 mg/l, 4 Hours > 5000 mg/kg 1237 mg/l, 120 Minutes	
Mouse		> 5000 mg/kg 1237 mg/l, 120 Minutes	
Mouse		1237 mg/l, 120 Minutes	
Mouse		1237 mg/l, 120 Minutes	
		-	
		-	
		-	
		-	
Rat			
Rat		52 %, 120 Minutes	
		1355 mg/l	
		658 mg/l/4h	
rolonaed skin (contact may cause t	temporary irritation	
ot a respirator	y sensitizer.		
Not available.			
Not available.			
his product is r	not considered to be	e a carcinogen by IARC, ACGIH, NTP, or OSHA.	
ubstances (2	9 CFR 1910.1001-1	050)	
· ·			
This product is not expected to cause reproductive or developmental effects.			
Not classified.			
Not classified.			
lay be fatal if s	wallowed and enter	s airways.	
armful to aqua	atic life with long last	ting effects.	
:	Species	Test Results	
S STEEL CLE	ANER(CAS Mixture	3)	
i0 /	Algae	23513 mg/L, 72 Hours	
50 I	Daphnia	6441 mg/L, 48 Hours	
50 I	Fish	160 ma/L. 96 Hours	
h c c c h c c la a si c 5	rect contact w ot a respirator of available. bis product is in ubstances (2 his product is in ot classified. bit classified.	rect contact with eyes may cause of a respiratory sensitizer. of available. of available. is product is not considered to be ubstances (29 CFR 1910.1001-1 his product is not expected to cause of classified. of classified. ay be fatal if swallowed and enter armful to aquatic life with long last <u>Species</u> S STEEL CLEANER(CAS Mixture O Algae 50 Daphnia	available. bit available. bit available. bit available. bits product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. bits product is not expected to cause reproductive or developmental effects. bit classified. bit classified. available. available. available. bit s product is not expected to cause reproductive or developmental effects. bit classified. bit classified. available. available. available. bit classified. available. available. available. bit classified. available. available. available. bit classified. available. available. bit classified. available. available.

Components		Species	Test Results
Distillates (Petroleum), Hydr	otreated Light (C	AS 64742-47-8)	
Aquatic			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.9 mg/l, 96 hours
Polydimethylsiloxane (CAS	63148-62-9)		
Aquatic			
Fish	LC50	Channel catfish (Ictalurus punctatus)	2.36 - 4.15 mg/l, 96 hours
rsistence and degradability	No data is av	ailable on the degradability of this product	
baccumulative potential	No data available.		
Partition coefficient n-octa	nol / water (log	Kow)	
Butane		2.89	
Propane	2.36		
bility in soil	No data available.		
her adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.		

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.		
Local disposal regulations	Dispose in accordance with all applicable regulations.		
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.		
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).		
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied.		

14. Transport information

DOT	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

ΙΑΤΑ

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
DOT	



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

I OXIC Substances Control Act (I SCA) Inventory Jilled States & Puerto Rico

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date

08-11-2014

Revision date Version #	10-13-2014 08
Disclaimer	The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision Information	Physical & Chemical Properties: Multiple Properties