

4184 E. Conant St. Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model # :		
Item #:	Qty:	
Available W/H :		
Approval :		

Vertical Open Display Cases

Full Heights Glass Side Panel

Model: TOM-50W(B)-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



Night Curtain (Standard)



Security Cover (Optional)



= FEATURES & BENEFITS =

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Safety reinforced tempered glass front shield and side walls optimize the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application.

- Designed to enhance impulsive sales
 Ideal for eye-catching displays and convenient access with fast
- service in high traffic area.
- Stainless steel solid shelves standard
- Standard back-guard improves airflow
- Energy saving night curtain standard
- Optional security cover available
- Foamed with polyurethane, high-density cell insulation (CFC free)
- Perforated interior back wall and top for improved airflow
- Front air intake and rear air discharge











Model	CU./FT.	# of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D x H (inches)
TOM-50W(B)-N	16.5	4	3/4 x 2	15.5	733	507/8 x 28 x 781/2

Vertical Open Display Cases

Model: TOM-50W(B)-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	○ NEMA 5-20P			
Full Load Amperes	15.5			
Compressor HP	3/4 x 2			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	16.5			
Ext. Length Overall (in.)	507/8 (1292mm)			
Ext. Depth Overall (in.)	28 (711mm)			
Ext. Height Overall (in.)	781/2 (1994mm)			
Int. Length Overall (in.)	483/8 (1229mm)			
Int. Depth Overall (in.)	141/4 (361mm)			
Int. Height Overall (in.)	497/8 (1267mm)			
# of Shelves	4			
Power Cord Length (in.)	591/8			
Net Weight (lbs.)	590			
Gross Weight (lbs.)	733			

Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

■ WARRANTY: 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

STANDARD FEATURES

- Simple plug-in installation
- · Patented self-contained system, no plumbing required
- · Solar powered digital thermometer
- · Digital electronic thermostat with defrost control
- · LED interior lighting
- Two color options available: White (W), black (B)

■ Recommended operating conditions


TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product. When used as a built-in, required clearance for the rear is 4" and the top is 5".

OPTIONAL ACCESSORIES


- 1.6" caster: CAS16WBT00 (non-brake)
- 4" caster. ½" diameter & 13 TPI: G8F6500101 (non-brake), G8F6500201 (w/ brake)
- 6" leveling seismic leg (1/2", 13 TPI): 30221M0700
- Security cover: SC-50 (White), SC-50B (Black), SCM-50 (White), SCM-50B (Black), SCS-50
- Price tag channel: P5000000ZK (481/4"L)

PLAN VIEW (unit: inch) Power Cord 507/8 (1292mm) 28 (711mm)

TOP VIEW



FRONT VIEW



Ver.20191113



■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519 ■ Warranty: 800-381-7770 ■ AC: 888-900-1002









