

Wrist Blade Handles

Model	Description
PM5	Faucet Wrist Blade Handles



PM5

Model	Description	Weight (lbs)
BG1101	Faucet Mounted Eyewash Unit with forged brass diverter valve, body has 55/64"-27 female inlet, furnished with three adaptors (15/16"-27, 13/16"-27 and 3/8" NPS) for installing on most commonly used faucets, including laboratory-type faucets, furnished with removable aerator on bottom	7



BG1101

Faucet-Mounted Eyewash Unit

- Converts most faucets into an emergency eyewash station without interfering with normal faucet operation
- Ideal for use with gooseneck faucets and can be installed at any sink
- Outlet heads are mounted 5" apart and deliver a soft, aerated flow of water
- Angle of heads is adjustable to permit full coverage and avoid splashing
- Meets ANSI Z358.1-2014

Wall and Deck Mount Spouts

Model	Description	Weight (lbs)
PMD8G	Deck Mount Spout, 8.5" gooseneck, triple chrome plated low lead brass alloy valve body, ceramic valve; polished chrome finished tubular brass spouts, 1/2" NPS male inlet with 1/4" NPT union tail piece and mounting hardware.	7
PMW8G	Wall Mount Spout, 8.5" gooseneck, triple chrome plated low lead brass alloy valve body, ceramic valve; polished chrome finished tubular brass spouts, 1/2" NPS female inlet, nipple, street well and mounting hardware.	7



PMD8G



PMW8G